

Effortlessly keeping your wood floor beautiful



All Dennebos engineered floor boards are finished with industrial Dennebos Hard Wax Oil, composed of high-quality natural ingredients.

Immediately after the floor has been installed it should be treated once with Dennebos Maintenance Oil transparent or white.

INSTRUCTIONS DENNEBOS MAINTENANCE OIL

- Dennebos Maintenance Oil (transparent/white) is best applied evenly and lengthwise along the wood grain with a short-haired mohair roller or a non-pilling cloth.
- Dennebos Maintenance Oil (transparent/white) may, if so desired, be polished immediately after application. This is done preferably by using a buffing machine with a white pad underneath.
- After application the oil needs approximately 12 – 14 hours to dry.

Depending on the intensity/load of the floor, daily maintenance by vacuum with a brush or by wiping the floor with a wiper (micro fibre) will do.

In addition you can clean your floor weekly with Dennebos Parquet Cleaner. Dennebos Parquet Cleaner is so composed that, when used according to the instructions, it does not corrode the oil finish and it does not leave any soap residue.

INSTRUCTIONS DENNEBOS PARQUET CLEANER

- Only add one cap of Dennebos Parquet Cleaner to a bucket of warm water (app. 10 litres). Then mop the floor with a slightly moist cloth, make sure no small pools of water are left.
- Stains or shoe-markings may be removed by applying Dennebos Parquet Cleaner undiluted to a non-pilling cloth and wipe out the stain lengthwise along the wood grain. Wipe immediately after treatment with lukewarm water.
- Should the floor become less beautiful when cleaning only with Dennebos Parquet Cleaner and it starts to show wear spots, the floor should be treated with Dennebos Maintenance Oil white or transparent, to re-saturate the wood.

Please note:

- Oiled wood floors are most vulnerable in the first 14 days after installation, because the oil has not yet fully hardened. For a complete and proper hardening it is important to spare your floor as much as possible. Please be extremely careful with water and moist.
- Dennebos Maintenance Oil white should only be used on floors with a last treatment of white oil.
- Please take care of proper ventilation during the drying time.
- The temperature of the room concerned should be between 15 – 22° Celsius.
- Relative humidity should be between 40 % and 65 %.
- Do not use any other cleaning agents, these generally leave a permanent film or they may affect the hard wax oil.

Dennebos Flooring B.V.
Almlosestraat 85 | 8102HC Raalte | THE NETHERLANDS

TEL +31-572 35-38 07 | FAX +31-572 35-15 26
info@dennebosflooring.com

dennebosflooring.com

Dennebos floors

easy to maintain



MAINTENANCE TIPS

- Wait at least 24 hours before putting on any furniture.
- Stick small pieces of felt or carpet underneath your furniture. This prevents scratches and damage when furniture is moved.
- Please do not cover the floor in the first two weeks, the hard wax oil needs two weeks to dry properly and completely.
- In the first two weeks the floor should only be vacuumed or cleaned with a dust cloth (like Swiffer for example), do not wipe with water.
- Wait at least 3-6 months before laying down carpets or rugs in order to prevent colouring.
- Provide proper door mats, both inside and out, at your front door. Less sand and dirt from outside will be dragged into your house, this will keep your floor longer free of scratches and damage.

MAINTENANCE ADVICE

- Clean your floor daily as dry as possible, vacuum with a brush, or even better, wipe it with a dust cloth (for example with Swiffer or micro fibre cloths). A floor wiper takes up more sand and dirt from the floor than a wet mop. If you do this daily you'll find that your floor shows fewer wear spots.
- If necessary, you may wipe the floor with a slightly moist cloth with warm/hot water, mixed with Dennebos Parquet Cleaner. Dennebos Parquet Cleaner cleans very thoroughly and at the same time feeds the wood, preventing the oil to wear away.
- When you drop or spill anything, it should be cleaned immediately with a slightly moist cloth with lukewarm water, which may be mixed with Dennebos Parquet Cleaner. Dry properly.
- Stains or shoe markings may be removed by applying Dennebos Parquet Cleaner undiluted to a non-pilling cloth and then wiping the stain lengthwise along the grain. Wipe off with lukewarm water immediately after treatment.
- Should the floor become less beautiful when only cleaning with Dennebos Parquet Cleaner and it starts to show wear spots, the floor should be treated with Dennebos Maintenance Oil white or transparent, to re-saturate the wood.